# Belief Change

# From AGM to Realistic Models

Andreas Herzig - herzig@irit.fr
IRIT
Université Paul Sabatier

Renata Wassermann - renata@ime.usp.br
Department of Computer Science
Universidade de São Paulo

©Herzig and Wassermann, 2001

# Course Outline

- **Lecture 1:** AGM Theory
- **Lecture 2:** Base Dynamics
- **Lecture 3:** New Trends in Revision
- **Lecture 4:** The theory of update
- **Lecture 5:** Computational models of update

©Herzig and Wassermann, 2001

# Belief Change — An example

(Gärdenfors & Rott 1995)

- Beliefs

  The bird caught in the trap is a swan
  The bird caught in the trap comes from Sweden
  Sweden is part of Europe
  All European swans are white

- Consequences

  The bird caught in the trap is white

- New information

  The bird caught in the trap is black

Which sentence(s) would you give up?

©Herzig and Wassermann, 2001 

# Motivation

Problem arises in several areas:

**Databases:** New entry inconsistent with database.

**Robotics:** Sensor information inconsistent with plans.

**Diagnosis:** Device behavior inconsistent with device description.

...

- Problem is not trivial:
  - Choice involved.
  - Indirect consequences of revision.
  - Representation issues.

©Herzig and Wassermann, 2001

# Desiderata

We are looking for belief change operations that

- follow certain principles of rationality:
  - minimal change.
  - categorical matching.
  - weak consistency.
- tolerate some inconsistency.
- are computationally tractable.

©Herzig and Wassermann, 2001

# Revision Versus Update

(Katsuno & Mendelzon)

- Revision: agent gets new information about static world.
  - Agent believes the book is either on the table or on the chair.
  - Agent is told the book is not on the table.
  - Agent believes the book is on the chair.
- Update: agent gets information about changes in the world.
  - Agent believes the book is either on the table or on the chair.
  - Agent is told that all objects that were on the table were removed from the room.
  - Agent believes that either the book is on the chair or it was removed from the room.

©Herzig and Wassermann, 2001 

# Lecture 1

# AGM Theory

©Herzig and Wassermann, 2001

# AGM Theory

**A**lchourrón, **G**ärdenfors, and **M**akinson (1985)

- Epistemic states: sets of formulas $K$.
- Epistemic attitudes:
  - $\alpha \in K$ - $\alpha$ accepted
  - $\neg\alpha \in K$ - $\alpha$ rejected
  - otherwise - $\alpha$ undetermined
- Input: formula
- Change operations: expansion, contraction, and revision.

©Herzig and Wassermann, 2001 

# Preliminaries

- Belief sets $K = Cn(K)$.
- Three operations:
  - Expansion ($K + \alpha = Cn(K \cup \{\alpha\})$)
  - Contraction ($K \dot{-} \alpha$)
  - Revision ($K * \alpha$)
- $K * \alpha = (K \dot{-} \neg\alpha) + \alpha$ (Levi identity)

For contraction and revision, rationality postulates.

©Herzig and Wassermann, 2001 

# Contraction Postulates

(**K-1**) $K \dot{-} \alpha$ is a belief set (*closure*)

(**K-2**) $K \dot{-} \alpha \subseteq K$ (*inclusion*)

(**K-3**) If $\alpha \notin K$, then $K \dot{-} \alpha = K$ (*vacuity*)

(**K-4**) If not $\vdash \alpha$, then $\alpha \notin K \dot{-} \alpha$ (*success*)

(**K-5**) If $\alpha \in K$, then $K \subseteq (K \dot{-} \alpha) + \alpha$ (*recovery*)

(**K-6**) If $\vdash \alpha \leftrightarrow \beta$, then $K \dot{-} \alpha = K \dot{-} \beta$ (*equivalence*)

©Herzig and Wassermann, 2001 

# Constructions for Contraction

- Partial Meet (AM)
- Safe Contraction (AM)
- Systems of Spheres (Grove)
- Epistemic Entrenchment (MG)

©Herzig and Wassermann, 2001

# Partial Meet Contraction – 1

- Let $K$ be a belief set and $\alpha$ a formula. For any set $X$, $X \in K \perp \alpha$ if and only if:
  - $X \subseteq Y$.
  - $X \nvdash \alpha$.
  - For all $X'$ such that $X \subset X' \subseteq K$, $X' \vdash \alpha$.
- A selection function $g$ must satisfy:
  - $g(K \perp \alpha) \subseteq K \perp \alpha$.
  - If $K \perp \alpha \neq \emptyset$, then $g(K \perp \alpha) \neq \emptyset$
    otherwise, $g(K \perp \alpha) = \{K\}$

©Herzig and Wassermann, 2001 

# Partial Meet Contraction – 2

Example: Let $K = Cn(p \wedge q)$

- $K \perp p = \{Cn(p \leftrightarrow q), Cn(q)\}$
- $K \perp p \wedge q = \{Cn(p), Cn(q), Cn(p \leftrightarrow q)\}$
- $K \perp p \rightarrow q = \{Cn(p), Cn(q)\}$

We may have:

- $g(K \perp p) = \{Cn(p \leftrightarrow q)\}$
- $g(K \perp p \wedge q) = \{Cn(p), Cn(q)\}$
- $g(K \perp p \rightarrow q) = \{Cn(p), Cn(q)\}$

©Herzig and Wassermann, 2001 

# Partial Meet Contraction – 3

**Definition:** Let $K$ be a belief set, $\alpha$ a formula, and $g$ a selection function. The partial meet contraction of $K$ by $\alpha$ is given by:

$$K \dot{-} \alpha = \bigcap g(K \perp \alpha).$$

**Theorem (AGM):** An operation $\dot{-}$ on K is a partial meet contraction if and only if it satisfies postulates (**K-1**)-(**K-6**).

©Herzig and Wassermann, 2001 

# Limit Cases – Full meet

- All elements of $K \perp \alpha$ are selected, that is:

$$K \dot{-} \alpha = \bigcap (K \perp \alpha).$$

  No choice involved.

- Problem: revision can lead to a set which is too small.

  If a revision operation is defined from full meet contraction by means of the Levi identity, then, for any $\alpha$ such that $\neg\alpha \in K$, $K * \alpha = Cn(\alpha)$.

©Herzig and Wassermann, 2001

# Limit Cases – Maxichoice

- Only one element of $K \perp \alpha$ is selected, that is:

$$K \dot{-} \alpha = \bigcap g(K \perp \alpha) \in K \perp \alpha.$$

- Problem: revision may lead to a set which is too big.

  If a revision operation is defined from a maxichoice contraction by means of the Levi identity, then, for any $\alpha$ such that $\neg\alpha \in K$, $K * \alpha$ will be maximal, i.e., for every formula $\beta$, either $\beta \in K * \alpha$ or $\neg\beta \in K * \alpha$.

©Herzig and Wassermann, 2001 

# Limit Cases – Examples

- Full meet: Suppose I believe that $p$ (Buenos Aires is the capital of Brazil) and that $q$ (there is no King of France). When I learn $\neg p$ and revise my belief set using a revision operation based on full meet contraction, I give up the belief that there is no King of France.
- Maxichoice: Suppose I believe $p$ (that Buenos Aires is the capital of Brazil) and have no idea about $q$ (that the King of France is bald). Finding out that $\neg p$ is the case and revising my belief set using a revision based on maxichoice contraction means that I will make a decision as to $q$ or $\neg q$.

©Herzig and Wassermann, 2001 

# Safe Contraction – 1

- Let $K$ be a belief set and $\alpha$ a formula. For any set $X$, $X \in K \perp\!\!\!\perp \alpha$ if and only if:
  - $X \subseteq Y$.
  - $X \vdash \alpha$.
  - For all $X'$ such that $X' \subset X \subseteq K$, $X' \nvdash \alpha$.
- Let $<$ be an acyclical hierarchy over $K$. An incision function $\sigma$ selects from each element of $K \perp\!\!\!\perp \alpha$ the minimal elment w.r.t. $<$:
  - $\sigma(K \perp\!\!\!\perp \alpha) \subseteq \bigcup(K \perp\!\!\!\perp \alpha)$.
  - If $X \in K \perp\!\!\!\perp \alpha$, $X \neq \emptyset$, $\beta$ minimal in $X$, then $\beta \in X \cap \sigma(K \perp \alpha)$.

©Herzig and Wassermann, 2001 

# Safe Contraction – 2

**Definition:** Let $K$ be a belief set, $\alpha$ a formula, and $\sigma$ an incision function. The safe contraction of $K$ by $\alpha$ is given by:

$$K \dot{-} \alpha = K \setminus \sigma(K \perp\!\!\!\perp \alpha).$$

**Theorem (AM85):** An operation $\dot{-}$ on K is a safe contraction if and only if it satisfies postulates (**K-1**)-(**K-6**).

©Herzig and Wassermann, 2001 

# Systems of Spheres – 1

Possible worlds semantics:

- $\mathcal{W}$ - set of all possible worlds (or truth assignments).
- $[\alpha] = \{w \in \mathcal{W} | w(\alpha) = 1\}$
- $[A] = \bigcap \{[\alpha] | \alpha \in A\}$
- $t(w) = \{\alpha | w(\alpha) = 1\}$
- $t(W) = \{\alpha | \forall w \in W, w(\alpha) = 1\}$ (Theory!)

©Herzig and Wassermann, 2001

# System of Spheres – 2

Let $S$ be a family of sets of possible worlds such that:

**(S1)** $S$ is totally ordered by $\subseteq$.
(If $U, V \in S$, then $U \subseteq V$ or $V \subseteq U$)

**(S2)** $[K]$ is the minimal element.
($[K] \in S$ and $\forall U \in S, [K] \subseteq U$)

**(S3)** $\mathcal{W}$ is the maximal element.

**(S4)** If any sphere intersects $[\alpha]$, then there is a sphere $c(\alpha)$ that is the smallest sphere intersecting $[\alpha]$).

Let $f(\alpha)$ denote $c(\alpha) \cap [\alpha]$.

©Herzig and Wassermann, 2001 

# Systems of Spheres – 3




©Herzig and Wassermann, 2001

# Systems of Spheres – Expansion




$$K + \alpha = t([K] \cap [\alpha])$$

©Herzig and Wassermann, 2001

# Systems of Spheres – Contraction




$$K \dot{-} \alpha = t([K] \cup f(\neg\alpha))$$

# Systems of Spheres – Revision




$$K * \alpha = t(f(\alpha))$$

©Herzig and Wassermann, 2001

# Systems of Spheres – Results

**Definition:** Let $K$ be a belief set and $\alpha$ a formula. The sphere contraction of $K$ by $\alpha$ is given by:

$$K\dot{-}\alpha = t([K] \cup f(\neg\alpha))$$

**Theorem (Grove 88):** An operator $\dot{-}$ is a sphere contraction if and only if it satisfies postulates (**K-1**)-(**K-6**) and

(**K-7**) $K\dot{-}\alpha \cap K\dot{-}\beta \subseteq K\dot{-}(\alpha \wedge \beta)$

(**K-8**) If $\alpha \notin K\dot{-}(\alpha \wedge \beta)$, then $K\dot{-}(\alpha \wedge \beta) \subseteq K\dot{-}\alpha$

©Herzig and Wassermann, 2001 

# Epistemic Entrenchment – 1

- (Transitivity) If $\alpha \leq_K \beta$ and $\beta \leq_K \gamma$, then $\alpha \leq_K \gamma$.
- (Dominance) If $\alpha \vdash \beta$, then $\alpha \leq_K \beta$.
- (Conjunctiveness) $\alpha \leq_K (\alpha \wedge \beta)$ or $\beta \leq_K (\alpha \wedge \beta)$.
- (Minimality) If $K \neq \bot$, then $\alpha \notin K$ if and only if $\alpha \leq_K \beta$ for all $\beta$.
- (Maximality) If $\beta \leq_K \alpha$ for all $\beta$, then $\vdash \alpha$.

©Herzig and Wassermann, 2001 

# Epistemic Entrenchment – 2

- **(C$\leq$)** $\alpha \leq_K \beta$ if and only if $\alpha \notin K\dot{-}(\alpha \wedge \beta)$ or $\vdash (\alpha \wedge \beta)$.
- **(C$\dot{-}$)** $\beta \in K\dot{-}\alpha$ if and only if $\beta \in K$ and either $\vdash \alpha$ or $\alpha \leq_K (\alpha \vee \beta)$.

**Theorem (GM88):** If an ordering $\leq$ satisfies **(EE1)-(EE5)**, then the contraction function determined by **(C$\dot{-}$)** satisfies **(K-1)-(K-8)** as well as condition **(C$\leq$)**.

**Theorem (GM88):** If a contraction operator $\dot{-}$ satisfies **(K-1)-(K-8)**, then the ordering $\leq$ that is determined by **(C$\leq$)** satisfies **(EE1)-(EE5)** as well as condition **(C$\dot{-}$)**.

©Herzig and Wassermann, 2001 

# Recovery: Example 1

(Hansson)

I believe that "Cleopatra had a son" ($\alpha$) and that "Cleopatra had a daughter" ($\beta$), and thus also that "Cleopatra had a child" ($\alpha \vee \beta$, briefly $\delta$). Then I receive information that makes me give up my belief in $\delta$, and contract my belief set accordingly, forming $K \dot{-} \delta$. Soon afterwards I learn from a reliable source that "Cleopatra had a child". It seems perfectly reasonable for me to then add $\delta$ (i.e. $\alpha \vee \beta$ ) to my set of beliefs without also reintroducing either $\alpha$ or $\beta$.

©Herzig and Wassermann, 2001 

# Recovery: Example 2

I previously entertained the two beliefs, "x is divisible by 2" ($\alpha$) and "x is divisible by 6" ($\beta$). When I received new information that induced me to give up the first of these beliefs ($\alpha$), the second ($\beta$) had to go as well (since $\alpha$ would otherwise follow from $\beta$).
Then I received new information that made me accept the belief "x is divisible by 8". ($\varepsilon$). Since $\alpha$ follows from $\varepsilon$, $(K \dot{-} \alpha) + \alpha$ is a subset of $(K \dot{-} \alpha) + \varepsilon$, then by recovery I obtain that "x is divisible by 24" ($\delta$), contrary to the intuition.

©Herzig and Wassermann, 2001 

# Success: Examples

(Fermé)

"Yesterday, the Pope called me to wish me good luck in the tutorial."

"Yesterday, my mother called me to wish me good luck in the tutorial."

One day when you return back from work, your son tells you, as soon as you see him: "A dinosaur has broken our Mings dynasty vase in the living-room". You probably accept one part of the information, namely that the vase has been broken, while rejecting the part of it that refers to a dinosaur.

Give up your belief in P $\neq$ NP, since you do not have a proof for it.

# Lecture 2

# Base Dynamics

©Herzig and Wassermann, 2001

# Bases

Problems with the use of logically closed belief sets:

- Infinite sets.
- Inconsistency leads to trivialization.
- Highest priority to incoming information.
- No distinction between explicit and implicit beliefs.

©Herzig and Wassermann, 2001

# Reasons for Using Belief Sets

- Syntax independence
  - what matters is the content, not the form.
- Knowledge level in AI
  - coexists with other levels of description.
- Logical elegance.

©Herzig and Wassermann, 2001

# Belief Bases (à la Hansson)

- Belief base $B$ finite set of formulas.
- Expansion: $B + \alpha = B \cup \{\alpha\}$.
- Epistemic attitudes:
  - $\alpha \in Cn(B)$: $\alpha$ (implicitly) believed.
  - $\alpha \in B$: $\alpha$ explicitly believed.
  - $\alpha \in Cn(B) \setminus B$: $\alpha$ merely derived.

©Herzig and Wassermann, 2001 

# Example (Hansson)

- $\alpha$: Paris is the capital of France.
- $\beta$: There is milk in the fridge.
- $\alpha, \beta \in B \Rightarrow \alpha \leftrightarrow \beta \in Cn(B)$

  When we revise by $\neg\beta$, we must choose between giving up $\alpha$ and $\alpha \leftrightarrow \beta$.

  In the belief base approach, $\alpha \leftrightarrow \beta$ is automatically chosen and $\alpha$ remains in the revised base (**"Disbelief Propagation"**).

# More advantages of the use of bases

**Expressivity** $B_1 = \{\alpha, \beta\}$, $B_2 = \{\alpha, \alpha \leftrightarrow \beta\}$.

$Cn(B_1) = Cn(B_2)$

$B_1 * \neg\alpha = \{\neg\alpha, \beta\}$

$B_2 * \neg\alpha = \{\neg\alpha, \alpha \leftrightarrow \beta\}$

$\beta \in Cn(B_1 * \neg\alpha)$, but $\beta \notin Cn(B_2 * \neg\alpha)$.

**Inconsistency Tolerance** $B_1 = \{p.\neg p, q_1, q_2, q_3\}$

$B_2 = \{p, \neg p, \neg q_1, \neg q_2, \neg q_3\}$

$Cn(B_1) = Cn(B_2)$, but $Cn(B_1 \dot{-} p) \neq Cn(B_2 \dot{-} p)$

©Herzig and Wassermann, 2001 

# Operations on Belief Bases

- **Expansion:** $B + \alpha = B \cup \alpha$
- **Contraction:**
  - Partial meet.
  - Kernel.
  - Prioritized.
- **Revision:**
  - Internal.
  - External.
- **New operations.**

©Herzig and Wassermann, 2001

# Partial Meet Base Contraction Construction

- $B \perp \alpha$: maximal subsets of $B$ that fail to imply $\alpha$
- $\gamma$: function that selects some elements of $B \perp \alpha$
- $B \dot{-}_{\gamma} \alpha = \bigcap \gamma(B \perp \alpha)$

©Herzig and Wassermann, 2001

# Partial Meet Base Contraction

# Postulates

- If $\alpha \notin Cn(\emptyset)$, then $\alpha \notin Cn(B \dot{-} \alpha)$ (success)
- $B \dot{-} \alpha \subseteq B$ (inclusion)
- If $\beta \in B \setminus (B \dot{-} \alpha)$, then there is some $B'$ such that $B \dot{-} \alpha \subseteq B' \subseteq B$, $\alpha \notin Cn(B')$ and $\alpha \in Cn(B' \cup \{\beta\})$ (relevance)
- If for all subsets $B'$ of $B$, $\alpha \in Cn(B')$ if and only if $\beta \in Cn(B')$, then $B \dot{-} \alpha = B \dot{-} \beta$ (uniformity)

©Herzig and Wassermann, 2001 

# Partial Meet Base Contraction

# Results

- Representation Theorem.
- Postulates not as intuitive as AGM.
- Recovery does not hold: $B = \{p \wedge q\}$, $(B \dot{-} p) + p = \{p\}$.
- Operation is really different from AGM. For example, maxichoice is not a problem for belief bases. It is actually often used in practice.

©Herzig and Wassermann, 2001 

# Kernel Contraction – Idea

- Generalization of safe contraction.
- No hierarchy of formulas.
- Selects at least one formula from every minimal set implying $\alpha$.
- Unlike AGM partial meet/safe contraction, kernel contraction is more general than partial meet.

©Herzig and Wassermann, 2001

# Kernel Base Contraction – Construction

- $B \perp\!\!\!\perp \alpha$: minimal subsets of $B$ that imply $\alpha$
- $\sigma$: function that selects at list one element of each set in $B \perp\!\!\!\perp \alpha$
- $B \dot{-}_{\sigma} \alpha = B \setminus \sigma(B \perp\!\!\!\perp \alpha)$

©Herzig and Wassermann, 2001

# Kernel Base Contraction – Postulates

- If $\alpha \notin Cn(\emptyset)$, then $\alpha \notin Cn(B \dot{-} \alpha)$ (success)
- $B \dot{-} \alpha \subseteq B$ (inclusion)
- If $\beta \in B \setminus B \dot{-} \alpha$, then there is some $B' \subseteq B$ such that $\alpha \notin Cn(B')$ and $\alpha \in Cn(B' \cup \{\beta\})$ (core-retainment)
- If for all subsets $B'$ of $B$, $\alpha \in Cn(B')$ if and only if $\beta \in Cn(B')$, then $B \dot{-} \alpha = B \dot{-} \beta$ (uniformity)

©Herzig and Wassermann, 2001 

# Contraction - Example

$B = \{p, p \vee q, p \leftrightarrow q\}$

$B \perp\!\!\!\perp (p \wedge q) = \{\{p, p \leftrightarrow q\}, \{p \vee q, p \leftrightarrow q\}\}$

$B \perp (p \wedge q) = \{\{p, p \vee q\}, \{p \leftrightarrow q\}\}$

$B \dot{-} (p \wedge q) = \{p\}$ can be constructed as kernel but not partial meet contraction.

©Herzig and Wassermann, 2001 

# Application – Diagnosis



# Application – Diagnosis

$$\begin{aligned} B = \quad & \{okX, okY, okZ, \\ & (A \wedge B) \wedge okX \rightarrow D, \neg(A \wedge B) \wedge okX \rightarrow \neg D, \\ & C \wedge okY \rightarrow \neg E, \neg C \wedge okY \rightarrow E, \\ & (D \vee E) \wedge okZ \rightarrow F, \neg(D \vee E) \wedge okZ \rightarrow \neg F\} \end{aligned}$$

$\mathrm{OBS} = \neg C \wedge \neg F$.

$B \perp\!\!\!\perp \neg\mathrm{OBS} = \{\{\neg C \wedge okY \rightarrow E, (D \vee E) \wedge okZ \rightarrow F, okY, okZ\}\}$

We have two possibilities for minimal incision functions:

$\sigma_1 = \{okY\}$ and $\sigma_2 = \{okZ\}$.

This means that either $Y$ or $Z$ are not working well.

©Herzig and Wassermann, 2001 

# Prioritized Bases – 1

Linear order (for example, temporal order):

- $B = (\alpha_1, \alpha_2, \ldots, \alpha_n)$
- $\alpha_i < \alpha_j$ for $i < j$
- $B_0 = \emptyset$

$$B_{i+1} = \begin{cases} B_i \cup \{\alpha_{i+1}\} & \text{if } B_i \cup \{\alpha_i\} \not\models \alpha \\ B_i & \text{otherwise} \end{cases}$$

$$B \dot{-} \alpha = B_n$$

OBS.: $(B \dot{-} \alpha) \in B \perp \alpha$, i.e., contraction is maxichoice.

Problem: Assumption that order is linear.

©Herzig and Wassermann, 2001 

# Prioritized Bases – 2

- Total pre-order $\leq$:
  - reflexive, transitive, and for all $\alpha, \beta$, either $\alpha \leq \beta$ or $\beta \leq \alpha$.
- $B$ is divided in equivalence classes w.r.t. $\leq$.
- From each class, we pick a maximal consistent subset not implying $\alpha$.
- Result of contraction is the union of the subsets of each class.

©Herzig and Wassermann, 2001 

# Prioritized Bases – Construction




©Herzig and Wassermann, 2001 

# Prioritized Bases – Construction 2

(Nebel)

$X \in B \Downarrow \alpha$ iff:

- $X = \bigcup X_i$
- $X_i \subseteq B_i$
- $X_i$ is a maximal subset of $B_i$ such that $\bigcup_{j \leq i} X_j \not\models \alpha$

$B \dot{-} \alpha = \bigcap (B \Downarrow \alpha)$

OBS.: $B \Downarrow \alpha \subseteq B \perp \alpha$, i.e., contraction is partial meet.

©Herzig and Wassermann, 2001 

# Revision of Belief Bases

- Levi Identity

  Internal revision:

  $B \mp \alpha = (B \dot{-} \neg\alpha) + \alpha$

- Reversed Levi Identity (Hansson)

  External revision:

  $B \pm \alpha = (B + \alpha) \dot{-} \neg\alpha$

  - Intermediate state may be inconsistent.

©Herzig and Wassermann, 2001

# Revision of Belief Bases – Examples

Let $B = \{p \to r, p \to \neg r\}$.

**(a) internal revision:** $B \bot \neg p = \{\{p \to r\}, \{p \to \neg r\}\}$, hence,
for $\gamma_1(B \bot \neg p) = \{\{p \to r\}\}$, we have $B \mp_{\gamma_1} p = \{p \to r, p\}$.

**(b) external revision:** $B + p \bot \neg p = \{\{p \to r, p\}, \{p \to \neg r, p\}\}$, hence,
for $\gamma_2(B + p \bot \neg p) = \{\{p \to \neg r, p\}\}$, we have $B \pm_{\gamma_2} p = \{p \to \neg r, p\}$.

©Herzig and Wassermann, 2001 

# Internal Partial Meet Revision

**(B*1)** If $\neg\alpha \notin Cn(\emptyset)$, then $\neg\alpha \notin Cn(B \mp \alpha)$ (non-contradiction)

**(B*2)** $B \mp \alpha \subseteq B \cup \{\alpha\}$ (inclusion)

**(B*3)** If $\beta \in B \setminus B \mp \alpha$, then there is some $B'$ such that $B \mp \alpha \subseteq B' \subseteq B \cup \{\alpha\}$, $\neg\alpha \notin Cn(B')$ but $\neg\alpha \in Cn(B \cup \{\beta\})$ (relevance)

**(B*4)** $\alpha \in B \mp \alpha$ (success)

**(B*5)** If for all $B' \subseteq B$, $\neg\alpha \in Cn(B')$ if and only if $\neg\beta \in Cn(B')$, then $B \cap (B \mp \alpha) = B \cap (B \mp \beta)$ (uniformity)

©Herzig and Wassermann, 2001 

# External Partial Meet Revision

**(B*1)** If $\neg\alpha \notin Cn(\emptyset)$, then $\neg\alpha \notin Cn(B \mp \alpha)$ (non-contradiction)

**(B*2)** $B \mp \alpha \subseteq B \cup \{\alpha\}$ (inclusion)

**(B*3)** If $\beta \in B \setminus B \mp \alpha$, then there is some $B'$ such that $B \mp \alpha \subseteq B' \subseteq B \cup \{\alpha\}$, $\neg\alpha \notin Cn(B')$ but $\neg\alpha \in Cn(B \cup \{\beta\})$ (relevance)

**(B*4)** $\alpha \in B \mp \alpha$ (success)

**(B*6)** If $\alpha$ and $\beta$ are elements of $B$ and it holds for all $B' \subseteq B$ that $\neg\alpha \in Cn(B')$ if and only if $\neg\beta \in Cn(B')$, then $B \cap (B \pm \alpha) = B \cap (B \pm \beta)$ (weak uniformity)

**(B*7)** $B + \alpha \pm \alpha = B \pm \alpha$ (pre-expansion)

©Herzig and Wassermann, 2001 

# Internal Kernel Revision

**(B*1)** If $\neg\alpha \notin Cn(\emptyset)$, then $\neg\alpha \notin Cn(B \mp \alpha)$ (non-contradiction)

**(B*2)** $B \mp \alpha \subseteq B \cup \{\alpha\}$ (inclusion)

**(B*3')** If $\beta \in B \setminus B \mp \alpha$, then there is some $B' \subseteq B$ such that $\neg\alpha \notin Cn(B')$ and $\neg\alpha \in Cn(B' \cup \{\beta\})$ (core-retainment)

**(B*4)** $\alpha \in B \mp \alpha$ (success)

**(B*5)** If for all $B' \subseteq B$, $\neg\alpha \in Cn(B')$ if and only if $\neg\beta \in Cn(B')$, then $B \cap (B \mp \alpha) = B \cap (B \mp \beta)$ (uniformity)

©Herzig and Wassermann, 2001 

# External Kernel Revision

**(B*1)** If $\neg\alpha \notin Cn(\emptyset)$, then $\neg\alpha \notin Cn(B \mp \alpha)$ (non-contradiction)

**(B*2)** $B \mp \alpha \subseteq B \cup \{\alpha\}$ (inclusion)

**(B*3')** If $\beta \in B \setminus B \mp \alpha$, then there is some $B' \subseteq B$ such that $\neg\alpha \notin Cn(B')$ and $\neg\alpha \in Cn(B' \cup \{\beta\})$ (core-retainment)

**(B*4)** $\alpha \in B \mp \alpha$ (success)

**(B*6)** If $\alpha$ and $\beta$ are elements of $B$ and it holds for all $B' \subseteq B$ that $\neg\alpha \in Cn(B')$ if and only if $\neg\beta \in Cn(B')$, then $B \cap (B \pm \alpha) = B \cap (B \pm \beta)$ (weak uniformity)

**(B*7)** $B + \alpha \pm \alpha = B \pm \alpha$ (pre-expansion)

©Herzig and Wassermann, 2001 

# Two New Operations

**Consolidation** Makes a belief base consistent.

$$B! = B \dot{-} \bot$$

**Semi-Revision** Non-prioritized revision, new info may be rejected.

$$B?\alpha = (B + \alpha)!$$

- Consolidation possible for bases because information is not lost in the presence of inconsistency.
- Different inconsistent bases react differently to the contraction by falsum.

# Lecture 3

# New Trends in Revision

©Herzig and Wassermann, 2001

# Topics:

- Non-prioritized revision.
- Relevance-based revision.
- Approximate belief revision.

©Herzig and Wassermann, 2001

# Non-prioritized Revision

- Input does not have highest priority and may be rejected.
- Decision + Revision:
  - Decide whether input should be accepted or rejected.
  - If accepted, then revise.
- Expansion + Consolidation:
  - Expand by the input.
  - Make expanded belief state consistent.
- Integrated Choice:
  - Choose (in one step) among the original beliefs and the input.

©Herzig and Wassermann, 2001

# Screened Revision

(Makinson, 1997)

$$K\#\alpha = \begin{cases} K *_A \alpha & \textit{if } \alpha \textit{ is consistent with } A \cap K \\ K & \textit{otherwise} \end{cases}$$

where $A$ is some set of sentences and $A \cap K \subseteq K *_A \alpha$

- Decide whether $\alpha$ should be accepted.
- Revise by $\alpha$.

©Herzig and Wassermann, 2001 

# Selective Revision

(Fermé and Hansson, 1998)

In some cases, parts of the input may be acccepted while other parts are rejected.

$$K?\alpha = K * f(\alpha)$$

where $f$ is a transformation function.

Usually, $\alpha \vdash f(\alpha)$.

©Herzig and Wassermann, 2001 

# Using Relevance

**Main idea:** Not all of the agent's belief are relevant.

**Example:** I believe it is always raining in Holland.
I see it is a sunny day in Amsterdam $\Rightarrow$ revision

The revision can be done without checking consistency with irrelevant beliefs.

# Example

Suppose I am at home and I hear on the radio that my friend Carol has been murdered yesterday night and that there were no traces of doors or windows having been forced. I talked to her yesterday on the phone and she was home with her flatmates Ann and Bill. I know that no one else, except for Ann, Bill and Carol has the keys to their apartment. I conclude that **Ann or Bill must have done it**. But I have known Ann for quite some time and cannot believe that she would be able to murder anyone. I believe **Ann did not do it**. For similar reasons, I believe **Bill did not do it**. This is clearly inconsistent with my belief that one of them did it. So I decide to visit my friend Paul to ask what he thinks. In front of his place I see **the lights are on**. I know that **if the lights are on, then Paul is home**. I get out of the car and Paul's neighbor, inferring that I am coming to visit him tells me **Paul is not home**. This is all very confusing, but I am sure of one thing: I do not believe **I am asleep**!

©Herzig and Wassermann, 2001 

# Compartments

$A$ compartment of $B$ = formulas of $B$ that contribute for (dis)proving some formula in $A$.

Formally: ($C$ inference operation)

- $B \perp\!\!\!\perp_C \alpha$ = minimal subsets $X$ of $B$ such that $\alpha \in C(B)$
- $c(\alpha, B) = \bigcup((B \perp\!\!\!\perp \alpha) \cup (B \perp\!\!\!\perp \neg\alpha) \setminus (B \perp\!\!\!\perp \bot))$
- $c(A, B) = \bigcup_{\alpha \in A} c(\alpha, B)$

©Herzig and Wassermann, 2001 

# Local Inference

$C_A(B) = Cn(c(A,B))$

$C_A(B)$ gives the classical consequences of those beliefs in $B$ which are relevant for the formulas in $A$.

- $C_A$ satisfies:
  - $B \subseteq B' \Rightarrow C_A(B) \subseteq C_A(B')$ (monotony)
  - $\alpha \in C_A(B) \Rightarrow$ there is $B' \subset B$, B' finite, s.t. $\alpha \in C_A(B')$ (compactness)
  - $C_A(C_A(B)) = C_A(B)$ (iteration)
- $C_A$ does not satisfy
  - $B \not\subseteq C_A(B)$ (inclusion)

©Herzig and Wassermann, 2001 

# Example revisited

Let $p$ stand for the proposition "Paul is at home",
$q$ for "The lights are on",
$a$ for "Ann is the murderer",
$b$ for "Bill is the murderer" and
$r$ for "I am asleep".

My belief base $B$ after talking to Paul's neighbor contains:

$$\{\neg p, q, q \to p, a \vee b, \neg a, \neg b, \neg r\}.$$

I am interested in whether Paul is at home, that is, the relevant beliefs are:

$$c(p, B) = \{q, q \to p, \neg p\}.$$

Even though this set is inconsistent we have that:

$$r \notin C_r(B) = Cn(c(r, B)) = Cn(\{\neg r\}).$$

©Herzig and Wassermann, 2001 

# Local Contraction

The local partial meet contraction operator based on a local inference operator $C_A$ and a selection function $\gamma$ is the operator $\dot{-}_{C_A,\gamma}$ such that:

$B\dot{-}_{C_A,\gamma}\alpha = \bigcap\gamma(B \perp_{C_A} \alpha)$.

Postulates:

- If $\alpha \notin C_A(\emptyset)$, then $\alpha \notin C_A(B\dot{-}\alpha)$ (success)
- $B\dot{-}\alpha \subseteq B$ (inclusion)
- If $\beta \in B \setminus (B\dot{-}\alpha)$, then there is some $B'$ such that $B\dot{-}\alpha \subseteq B' \subseteq B$, $\alpha \notin C_A(B')$ and $\alpha \in C_A(B' \cup \{\beta\})$ (relevance)
- If for all subsets $B'$ of $B$, $\alpha \in C_A(B')$ if and only if $\beta \in C_A(B')$, then $B\dot{-}\alpha = B\dot{-}\beta$ (uniformity)

©Herzig and Wassermann, 2001 

# Structured Bases

- Problems:
  - Finding the compartments is very expensive.
  - There is no guaranty that the compartment will be small.
- But: Representation results do not depend on the way the compartments are found!
- So: Look for more efficient method.
- Idea: Organize belief base as a graph, where links represent relevance.

# Relevance Graph




$\mathcal{R}(\varphi, \psi)$ if and only if $\varphi$ and $\psi$ share an atom

©Herzig and Wassermann, 2001 

# Alternative for Compartments

**Definition:** Formulas of $B$ relevant for $\alpha$ up to degree $n$:

$\Delta^n(\alpha, B) = \{\varphi \in B | d(\alpha, \varphi) \leq n\}$

Set of relevant formulas for $\alpha$: $\Delta^{\leq\omega}(\alpha, B) = \bigcup_{i \geq 0} \Delta^i(\alpha, B)$

**Proposition:** Let $B$ be a belief base and $\alpha$ a formula. The local inference operations $C^n_\alpha(B) = Cn(\Delta^{\leq n}(\alpha, B))$ are compact and monotonic.

So: $\Delta^{\leq n}$ can be used for local change.

# Computational Aspects – 1

- Retrieval can be done in linear time.
- Anytime method: anytime the algorithm is interrupted, it returns the most relevant beliefs.
- Ideal case - the algorithm returns the connected subgraph $\Delta^{\leq\omega}(\alpha, B)$

©Herzig and Wassermann, 2001

# Computational Aspects – 2



# Example re-revisited

My belief base *B* after talking to Paul's neighbor contains:



# Example re-revisited – 2

I am interested in whether Paul is at home, that is, the relevant beliefs are:

$$\Delta^{\leq\omega}(p, B) = \{q, q \rightarrow p, \neg p\}.$$

Even though this set is inconsistent we have that:

$$r \notin C_r^{\omega}(B) = Cn(\Delta^{\leq\omega}(r, B)) = Cn(\{\neg r\}).$$

©Herzig and Wassermann, 2001 

# Approximate Entailment – Cadoli and Schaerf

**Main idea:** Consider only some propositional letters.

- $L$: propositional letters of the language.
- Context set $S \subseteq L$.
- Define two approximate entailments:
  - $\models^1_S$: complete but not sound.
  - $\models^3_S$: sound and incomplete.
- $S = L$: classical entailment.
- Approximations behave classically for $x \in S$.
  - $S_1$ assignment: if $x \notin S$, then $x, \neg x$ both false.
  - $S_3$ assignment: if $x \notin S$, then $x, \neg x$ not both false.

©Herzig and Wassermann, 2001 

# Example – Cadoli and Schaerf

$B =$ $\{\neg$cow $\vee$ grass-eater, $\neg$dog $\vee$ carnivore,
$\neg$grass-eater $\vee$ $\neg$has-canine-teeth,
$\neg$grass-eater $\vee$ mammal,
$\neg$carnivore $\vee$ mammal,
$\neg$mammal $\vee$ has-canine-teeth $\vee$ has-molar-teeth,
$\neg$mammal $\vee$ vertebrate,
$\neg$vertebrate $\vee$ animal$\}$.

Let $\alpha = \neg$cow $\vee$ has-molar-teeth.

$B \models \alpha$?

For $S =$ $\{$grass-eater, mammal, has-canine-teeth$\}$,

$B \models^3_S \alpha$, hence $B \models \alpha$.

©Herzig and Wassermann, 2001 

# Approximate Belief Revision

(Chopra, Parikh, Wassermann, WOLLIC 2000)

- Goal:
  - Local change.
  - Inconsistency tolerance.
  - Computational feasibility.
  - Logical elegance.
- Proposal: Integrate approximate inference relations with Local Change model.

©Herzig and Wassermann, 2001 

# Recap: Local Contraction

- Definition: Let $C$ be an inference operation on $L$ and $\sigma$ an incision function. The local kernel contraction of $B$ determined by $C$ and $\sigma$ is the operation $\dot{-}_{C,\sigma}$ such that $\forall B$: $B\dot{-}_{C,\sigma}\alpha = B \setminus \sigma(B \perp\!\!\!\perp_C \alpha)$
- Theorem: Let $C$ be an inference operation satisfying monotonicity and compactness. Then $\dot{-}$ is an operation of local kernel contraction determined by $C$ and some incision function iff $\forall B$ :
  - If $\alpha \notin C(\emptyset)$, then $\alpha \notin C(B\dot{-}\alpha)$ (success)
  - $B\dot{-}\alpha \subseteq B$ (inclusion)
  - If $x \in B \setminus B\dot{-}\alpha$, then there is some $B' \subseteq B$ such that $\alpha \notin C(B')$ and $\alpha \in C(B' \cup \{x\})$ (core-retainment)
  - If for all subsets $B'$ of $B$ $\alpha \in C(B')$ if and only if $\beta \in C(B')$, then $B\dot{-}\alpha = B\dot{-}\beta$ (uniformity)

©Herzig and Wassermann, 2001 

# Approximating Belief Change

- $C_S^i(B) = \{\alpha | B \models_S^i \alpha\}$
- Proposition: Let $S$ be a fixed set of propositional variables. Then $C_S^i$ satisfies monotony and compactness.
- Corollary: $C_S^i$ can be used for local change.
- Approximate kernel contraction of $B$ determined by $C_S^i$:
  - $B \dot{-}_{C_S^i,\sigma} \alpha = B \setminus \sigma(B \perp\!\!\!\perp_{C_S^i} \alpha)$
- **Result:** two kinds of contraction operations:
  - one more radical (based on $S_1$)
  - one more cautious (based on $S_3$)

©Herzig and Wassermann, 2001 

# Problem: Choice of $S$

- Suggestion: Use some notion of relevance.
- For example, syntactic relevance:
- $R(p,q,B)$ iff $p$ and $q$ appear in the same formula of $B$.

  Construction strategy for $S$:
  - Start with $L(\alpha)$.
  - Test entailments.
  - If the result is not satisfactory and resources are available, add to $S$ the atoms relevant to elements in $S$ and go to 2.
  - Return approximations.

©Herzig and Wassermann, 2001 

# Example – Hans the student

$B =$ $\{\texttt{student}, \neg\texttt{student} \vee \texttt{young},$
$\neg\texttt{young} \vee \neg\texttt{pensioner}, \texttt{worker},$
$\neg\texttt{worker} \vee \neg\texttt{pensioner}, \texttt{blue-eyes},$
$\texttt{likes-dancing}, \texttt{six-feet-tall}\}.$

- Start with $S$=$\{\texttt{pensioner}\}$:
  - $B \perp\!\!\!\perp_{C_S^3} \neg\texttt{pensioner} = \emptyset$.
- $S$= $\{\texttt{pensioner}, \texttt{young}, \texttt{worker}\}$
  - $B \perp\!\!\!\perp_{C_S^3} \neg\texttt{pensioner} = \{\{\texttt{worker}, \neg\texttt{worker} \vee \neg\texttt{pensioner}\}\}$.
- $S$=$\{\texttt{pensioner}, \texttt{young}, \texttt{worker}, \texttt{student}\}$
  - $B \perp\!\!\!\perp_{C_S^3} \neg\texttt{pensioner} = \{\{\texttt{student}, \neg\texttt{student} \vee \texttt{young},$
    $\neg\texttt{young} \vee \neg\texttt{pensioner}\}, \{\texttt{worker}, \neg\texttt{worker} \vee \neg\texttt{pensioner}\}\}$.

©Herzig and Wassermann, 2001 

# To Conclude

What have we done?

- Started from classical AGM theory
- Proceeded in the direction of more applicable methods:
  - Belief Bases
  - Models based on relevance
  - Approximations

©Herzig and Wassermann, 2001

# Course Outline

- **Lecture 1:** AGM Theory
- **Lecture 2:** Base Dynamics
- **Lecture 3:** New Trends in Revision
- **Lecture 4:** The theory of update
- **Lecture 5:** Computational models of update

©Herzig and Wassermann, 2001

# Lecture 4

# The Theory of Update

material from (Herzig 1998): **revised** and **updated**

- updates vs. revisions
- world-wise change
- updates vs. conditionals: the Ramsey test
- logics based on the Ramsey test

©Herzig and Wassermann, 2001 

# Is every belief change of AGM type?

- beliefs

  The window is open or the door is open.

- new information

  Somebody closes the door.

- belief change according to AGM

  The window is open.

**Revision does not apply here!**

# Where does AGM-revision apply?

- scientific theories (Gärdenfors, Segerberg)
  - 'theory revision'
  - small changes only (no paradigm shifts)
- regulations (Alchourrón)
  - derogations in legal systems
- diagnosis
- commonsense reasoning???
- databases???
- reasoning about actions and events???

©Herzig and Wassermann, 2001

# Two distinct operations

(Keller & Winslett 1985)

- beliefs

  I believe Kaurismäki lives in Finland.

- What changes?

  1. recording of change in the world:

     I learn that he has just moved to Hollywood.

     - update

  2. new information about an unchanged world:

     I learn that I have been mistaken and that he lives in Hollywood.

     - revision

# World-wise change – the idea

(Katsuno & Mendelzon, KR 1991)

- interpretation of a belief set $B$
  = set of possible worlds where $B$ is true
  (may contain the real world, but need not)
- notification of some change in the real world
- The description of the possible states of affairs must be modified accordingly:

  *Since we are confined to our set of possibilities, we must make the change come true in all of our candidate worlds. Semantically, we change each of the possible worlds 'as little as possible' in order to make the new state of affairs hold. (Grahne, KR 1991)*

models?

©Herzig and Wassermann, 2001 

# World-wise change – selection functions

- interpretation of $B = \{w | w \text{ is a possible world, and } w \models B\}$
  $= [B]$
- update of a world $w \in [B]$ by $A$
  - = the possible worlds close to $w$ where $A$ is true
  - = $w \cdot [A]$ (selection function)




©Herzig and Wassermann, 2001 

# Selection function semantics

update of $B$ by $A \;=\; [B{\leftarrow\!\diamond}A] \;=\; \bigcup_{w\in[B]} w\cdot[A]$




**postulates? properties? constructions?**

©Herzig and Wassermann, 2001 

# Updates vs. conditionals

- update problem: given
  - current belief base $B$,
  - input $A$,
  - a belief $C$,

  does $C$ result from updating $B$ by $A$?
- ternary relation $\mathcal{R}(B,A,C)$; algebraically:
  1. $\mathcal{R}(B,A,C)$ iff $B \leftarrow\!\diamond A \vdash C$
     $B \leftarrow\!\diamond A$ "$B$ has been updated by $A$"
     'looking back'; used in databases
  2. $\mathcal{R}(B,A,C)$ iff $B \vdash A \mathrel{\Box\!\!\rightarrow} C$
     $A \mathrel{\Box\!\!\rightarrow} C$ "if one updates with $A$ then $C$ follows"
     'looking forward'; studied in philosophical logic

©Herzig and Wassermann, 2001 

# Updates vs. conditionals – the Ramsey test

$$B \leftarrow\!\diamond A \vdash C \text{ iff } B \vdash A \mathbin{\Box\!\!\rightarrow} C$$

*If two people are arguing 'If p will q and are both in doubt as to p, they are adding p hypothetically to their stock of knowledge and arguing on that basis about q.* *(Ramsey 1931)*

*This is how to evaluate a conditional: First, add the antecedent (hypothetically) to your stock of beliefs; second, make whatever adjustments are required to maintain consistency (without modifying the hypothetical belief in the antecedent); finally, consider whether or not the consequent is then true.* *(Stalnaker 1968)*

©Herzig and Wassermann, 2001 

# Updates vs. conditionals: Gärdenfors' impossibility theorem – 1

(Gärdenfors 1978)

**Theorem:** Suppose

- $\longleftrightarrow\!\!\diamond$ is a metalanguage belief change operation (mapping bases and inputs to new bases)
- $\mathcal{L}$ is a logic for an (object language) $\Box\!\!\rightarrow$
- $\longleftrightarrow\!\!\diamond$ and $\Box\!\!\rightarrow$ satisfy the Ramsey test:

$$B \longleftrightarrow\!\!\diamond A \vdash C \text{ iff } \vdash_{\mathcal{L}} B \rightarrow (A \Box\!\!\rightarrow C)$$

- the logic is 'rich enough'

Then $\longleftrightarrow\!\!\diamond$ does not satisfy the AGM postulates.

©Herzig and Wassermann, 2001 

# Gärdenfors' impossibility theorem – 2

Let $A_1 \wedge A_2$, $\neg(A_1 \wedge A_2)$, etc. be all consistent. (L is rich enough.)

Let $B$ be ignorant w.r.t. $A_1$ and $A_2$, i.e. $B \not\vdash A_1$, $B \not\vdash \neg A_1$, $B \not\vdash A_2$, $B \not\vdash \neg A_2$.

Suppose $\leftarrow\!\diamond$ satisfies the AGM postulates, and let
$B_1 = B\leftarrow\!\diamond A_1$, $B_2 = B\leftarrow\!\diamond A_2$, $B_{12} = B\leftarrow\!\diamond(A_1 \wedge A_2)$.

1. $B_1 \leftrightarrow B \wedge A_1$, and $B_2 \leftrightarrow B \wedge A_2$ because $\leftarrow\!\diamond$ satisfies AGM
2. $B_1\leftarrow\!\diamond\neg(A_1 \wedge A_2) \leftrightarrow B \wedge A_1 \wedge \neg A_2$, and $B_2\leftarrow\!\diamond\neg(A_1 \wedge A_2) \leftrightarrow B \wedge \neg A_1 \wedge A_2$
   again because $\leftarrow\!\diamond$ satisfies AGM
3. $\vdash_{\mathcal{L}} B_1 \rightarrow \neg(A_1 \wedge A_2)\Box\!\!\rightarrow A_1$, and $\vdash_{\mathcal{L}} B_2 \rightarrow \neg(A_1 \wedge A_2)\Box\!\!\rightarrow A_2$
   by the Ramsey test
4. $B_{12} \leftrightarrow B \wedge A_1 \wedge A_2$ because $\leftarrow\!\diamond$ satisfies AGM
5. $B_{12} \rightarrow B_1$ and $B_{12} \rightarrow B_2$ with 1
6. $\vdash_{\mathcal{L}} B_{12} \rightarrow (\neg(A_1 \wedge A_2)\Box\!\!\rightarrow A_1)$, and $\vdash_{\mathcal{L}} B_{12} \rightarrow (\neg(A_1 \wedge A_2)\Box\!\!\rightarrow A_2)$ with 3

©Herzig and Wassermann, 2001 

# Gärdenfors' impossibility theorem – 3

7. $(B_{12} \leftarrow\!\diamond \neg(A_1 \wedge A_2)) \rightarrow A_1$, and $(B_{12} \leftarrow\!\diamond \neg(A_1 \wedge A_2)) \rightarrow A_2$
   again by the Ramsey test
8. $B_{12} \leftarrow\!\diamond \neg(A_1 \wedge A_2) \rightarrow (A_1 \wedge A_2)$ from 7
9. $B_{12} \leftarrow\!\diamond \neg(A_1 \wedge A_2) \rightarrow \bot$ because $\leftarrow\!\diamond$ satisfies AGM
10. ...but $B_{12} \leftarrow\!\diamond \neg(A_1 \wedge A_2)$ should be consistent (because $A_1 \wedge A_2$ is consistent)

**Remarks:**

1. Gärdenfors' result does not depend on $\vdash$, and the theorem holds even if $\vdash$ is a substructural or nonmonotonic logic (Makinson, SL 1990)
2. similar to Gödel's incompleteness result: no object language predicate can express consistency
3. does not hold for updates (Grahne, KR 1991)

©Herzig and Wassermann, 2001 

# Rest of lecture 4:

# Logics based on the Ramsey test

- language vs. metalanguage
- taking the Ramsey test seriously
- some derivable principles
- normal update logics
- cumulative update logics
- the KM-theory as an extension

©Herzig and Wassermann, 2001 

# Language vs. metalanguage

- traditionally:
  - $\leftarrow\!\diamond$ metalanguage operation
    - single model
    - non-constructive postulates
      "if $A$ consistent then $B \leftarrow\!\diamond A$ consistent", ...
  - $\leftarrow\!\diamond$ object language operator
    - classes of models
    - axiomatics (constructive)
- here:
  - two dyadic modal operators in the object language
    - update operator: $\leftarrow\!\diamond$
    - conditional operator: $\Box\!\rightarrow$

©Herzig and Wassermann, 2001 

# Taking the Ramsey test seriously

- classical logic, plus
- . . . just two inference rules: "the Ramsey rules"
  - $\dfrac{B \leftarrow\!\diamond A \ \rightarrow\ C}{B \ \rightarrow\ A \Box\!\rightarrow C}$
  - $\dfrac{B \ \rightarrow\ A \Box\!\rightarrow C}{B \leftarrow\!\diamond A \ \rightarrow\ C}$

©Herzig and Wassermann, 2001 

# Updates and conditionals as inverse modal operators

(Ryan & Schobbens, JoLLI 1997)

**Switching Lemma (de Rijke, Venema, Roorda, Dunn):**

- The conversion axioms
  - $B \rightarrow A \Box\!\!\rightarrow (B \leftarrow\!\!\Diamond A)$
  - $(A \Box\!\!\rightarrow C) \leftarrow\!\!\Diamond A \rightarrow C$

  can be derived from the Ramsey rules
- . . . and vice versa

cf. tense logics, dynamic logic with inverse modality $\alpha^{-1}$, program logics:

$$A \Box\!\!\rightarrow C = \overrightarrow{\Box}_A C$$

$$B \leftarrow\!\!\Diamond A = \overleftarrow{\Diamond}_A B$$

©Herzig and Wassermann, 2001 

# Derivable principles for updates – 1

- syntax-independence

$$\frac{B_1 \leftrightarrow B_2}{B_1 \leftarrow\!\diamond A \leftrightarrow B_2 \leftarrow\!\diamond A}$$

- monotony

$$\frac{B_1 \rightarrow B_2}{B_1 \leftarrow\!\diamond A \rightarrow B_2 \leftarrow\!\diamond A}$$

- updating disjunctions

$$(B_1 \leftarrow\!\diamond A \vee B_2 \leftarrow\!\diamond A) \leftrightarrow (B_1 \vee B_2) \leftarrow\!\diamond A$$

- inconsistency preservation

$$\bot \leftarrow\!\diamond A \rightarrow \bot$$

©Herzig and Wassermann, 2001 

# Derivable principles for updates – 2

- example: proof of $\bot \leftarrow\!\diamond A \;\rightarrow\; \bot$

| | |
|---|---|
| 1. $\bot \;\rightarrow\; A \Box\!\rightarrow \bot$ | by classical logic |
| 2. $\bot \leftarrow\!\diamond A \;\rightarrow\; \bot$ | by the Ramsey rules |

- example: proof of $\dfrac{B_1 \;\equiv\; B_2}{B_1 \leftarrow\!\diamond A \;\equiv\; B_2 \leftarrow\!\diamond A}$

| | |
|---|---|
| 1. $B_1 \equiv B_2$ | hypothesis |
| 2. $\dfrac{B_1 \;\rightarrow\; A \Box\!\rightarrow C}{B_2 \;\rightarrow\; A \Box\!\rightarrow C}$ | from 1, with fresh $C$ |
| 3. $\dfrac{B_1 \leftarrow\!\diamond A \;\rightarrow\; C}{B_2 \leftarrow\!\diamond A \;\rightarrow\; C}$ | from 2, by the Ramsey rules |
| 4. $B_2 \leftarrow\!\diamond A \;\rightarrow\; B_1 \leftarrow\!\diamond A$ | from 3 |
| 5. $B_1 \leftarrow\!\diamond A \;\rightarrow\; B_2 \leftarrow\!\diamond A$ | with a proof similar to 1–4 |

©Herzig and Wassermann, 2001

# Derivable principles for conditionals

(Wansing, JLC 1994)

- $$\frac{A_1 \leftrightarrow A_2}{A_1 \Box\!\!\rightarrow C \leftrightarrow A_2 \Box\!\!\rightarrow C}$$
- $$\frac{C_1 \leftrightarrow C_2}{A \Box\!\!\rightarrow C_1 \leftrightarrow A \Box\!\!\rightarrow C_2}$$
- $$\frac{C_1 \rightarrow C_2}{A \Box\!\!\rightarrow C_1 \rightarrow A \Box\!\!\rightarrow C_2}$$
- $A \Box\!\!\rightarrow (C_1 \wedge C_2) \leftrightarrow (A \Box\!\!\rightarrow C_1 \wedge A \Box\!\!\rightarrow C_2)$
- $A \Box\!\!\rightarrow \top$

**axioms of semi-normal conditional logic Ck (Chellas, JPL 1975)**

©Herzig and Wassermann, 2001 

# Recovering normal conditional logics

CK (C "conditional", K "Kripke")

$$= \text{Ck} + \frac{A_1 \leftrightarrow A_2}{A_1 \Box\!\!\rightarrow C \leftrightarrow A_2 \Box\!\!\rightarrow C}$$

- selection function semantics:
  - $M = \langle W, \cdot, V \rangle$ such that
    - $W$ (possible worlds)
    - $\cdot : W \times 2^W \longrightarrow 2^W$ (selection function)
    - $V(w) \subseteq ATM$ for all $w \in W$ (truth assignment)
  - $[A \Box\!\!\rightarrow C] = \{w \in W | w \cdot [A] \subseteq [C]\}$

**Theorem (Chellas, JPL 1975):** sound and complete, finite model property, decidable

©Herzig and Wassermann, 2001 

# The other way round:

- given
  - a conditional logic $\mathcal{L}_{\Box\rightarrow}$
  - its tense extension $\mathcal{L}_{\Box\rightarrow,\leftarrow\Diamond}$ by the Ramsey rules
- which properties does $\mathcal{L}_{\Box\rightarrow}$ inherit? (completeness, decidability, finite model, correspondence)

- ALL if $\mathcal{L}$ is one of the standard systems
- CORRESPONDENCE ONLY in the general case (Wolter, NDJFL 1998)

©Herzig and Wassermann, 2001 

# Normal update logics

UCK (U "update", C "conditional", K "Kripke")

= CK + Ramsey rules

= classical logic + Ramsey rules + $\dfrac{A_1 \leftrightarrow A_2}{A_1 \Box\!\!\rightarrow C \leftrightarrow A_2 \Box\!\!\rightarrow C}$

= classical logic + Ramsey rules + $\dfrac{A_1 \leftrightarrow A_2}{B \leftarrow\!\!\Diamond A_1 \leftrightarrow B \leftarrow\!\!\Diamond A_2}$

**Theorem (Herzig 1998):** sound and complete for selection function semantics.

$[B \leftarrow\!\!\Diamond A] = \bigcup_{w \in [B]} w \cdot [A]$ $\qquad$ $[A \Box\!\!\rightarrow C] = \{w \in W \mid w \cdot [A] \subseteq [C]\}$

©Herzig and Wassermann, 2001 

# Four desiderata for belief update

- syntax-independence
  - if $A_1 \leftrightarrow A_2$ then $B \leftarrow\!\!\diamond A_1$ equivalent to $B \leftarrow\!\!\diamond A_2$
  - if $B_1 \leftrightarrow B_2$ then $B_1 \leftarrow\!\!\diamond A$ equivalent to $B_2 \leftarrow\!\!\diamond A$
- success
  - $B \leftarrow\!\!\diamond A \vdash A$
- consistency 'as much as possible'
  - $B \leftarrow\!\!\diamond A$ is consistent iff both $B$ and $A$ are consistent.
- minimal change
  - $B \leftarrow\!\!\diamond A$ is 'as close to $B$ as possible'

**the latter 3 require extensions of UCK . . .**

©Herzig and Wassermann, 2001 

# UCK and the desiderata – 1

- success
  - axiomatically:
    UCK $+ B \leftarrow\!\!\diamond A \rightarrow A$ alternative: $+ A \Box\!\!\rightarrow A$
  - semantically: $w \cdot [A] \subseteq [A]$
- consistency 'as much as possible'
  - axiomatically:
    UCK $+ \dfrac{B \leftarrow\!\!\diamond A \rightarrow \bot}{B \rightarrow \bot}$ alternative: $+ \neg(A \Box\!\!\rightarrow \bot)$
  - semantically: $w \cdot [A] \neq \emptyset$, for all $w \in W$

for every consistent formula of classical logic $A$

©Herzig and Wassermann, 2001 

# UCK and the desiderata – 2

- minimal change
  - axiomatically: difficult to express if $B \wedge A$ is inconsistent
  - semantically: minimal change 'defined away' by selection function
- but weaker forms of minimal change
  - UCK + $\dfrac{B \rightarrow A}{B \leftarrow\!\!\diamond A \leftrightarrow B}$ (idempotence)
  - ...

**minimality $\sim$ orderings ...**

©Herzig and Wassermann, 2001 

# Cumulative update logics

minimal change: orderings of closeness associated to worlds




©Herzig and Wassermann, 2001

# Cumulative update logics – semantics

- $M = \langle W, \{ \leq_w | w \in W \}, V \rangle$ such that
  - $W$ some set (possible worlds)
  - $\leq_w$ partial pre-order on $W$ (reflexive and transitive relation)
    $u \leq_w v$ = "$u$ is at least as close to $w$ as $v$ is"
  - $V(w)$ truth assignment
- $S_w = \{u \in W |$ there is $v \in W$ such that $u \leq_w v\}$ (accessible worlds)
- $w \cdot [A]$ = the $A$-worlds closest to $w$
  $= \min_{\leq_w}([A] \cap S_w)$
  $= \{u \in [A] \cap S_w |$ for all $v \in [A] \cap S_w$, if $v \leq_w u$ then $u \leq_w v\}$
- truth conditions as for UCK
- if $W$ infinite: Limit Assumption; guarantees that $[A] \neq \emptyset$ implies $w \cdot [A] \neq \emptyset$

©Herzig and Wassermann, 2001 

# Cumulative conditional logics – axiomatics

CL (C "conditional", L "Lewis")

$=$ CK

$+ \; A \Box\!\!\rightarrow A$

$+ \; ((A_1 \Box\!\!\rightarrow C) \wedge (A_2 \Box\!\!\rightarrow C)) \rightarrow ((A_1 \vee A_2) \Box\!\!\rightarrow C)$

$+ \; ((A_1 \Box\!\!\rightarrow A_2) \wedge (A_2 \Box\!\!\rightarrow A_1)) \rightarrow ((A_1 \Box\!\!\rightarrow C) \leftrightarrow (A_2 \Box\!\!\rightarrow C))$

(Lewis 1973, Burgess 1981)

©Herzig and Wassermann, 2001 

# Cumulative update logics – axiomatics

UCL (U "update", C "conditional", L "Lewis")

$= \text{UCK} + \text{CL}$

$= \text{UCK}$

$+ \ (B \leftarrow\!\diamond A) \ \rightarrow \ A$

$+ \ (B \leftarrow\!\diamond (A_1 \vee A_2)) \ \rightarrow \ ((B \leftarrow\!\diamond A_1) \vee (B \leftarrow\!\diamond A_2))$

$+ \ \dfrac{(B \leftarrow\!\diamond A_1) \rightarrow A_2 \ , \ (B \leftarrow\!\diamond A_2) \rightarrow A_1}{(B \leftarrow\!\diamond A_1) \leftrightarrow (B \leftarrow\!\diamond A_2)}$

©Herzig and Wassermann, 2001 

# UCL: derivable principles

- cumulativity
  - $(A_1 \Box\!\!\rightarrow A_2) \rightarrow ((A_1 \Box\!\!\rightarrow C) \leftrightarrow (A_2 \Box\!\!\rightarrow C))$
  - $$\frac{B \leftarrow\!\!\Diamond A_1 \rightarrow A_2}{(B \leftarrow\!\!\Diamond A_1) \leftrightarrow (B \leftarrow\!\!\Diamond A_1 \wedge A_2))}$$
- ...

©Herzig and Wassermann, 2001 

# KM theory

(**K**atsuno & **M**endelzon, KR 1991)

- A KM-model is a UCL-model $M = \langle W, \{ \leq_w | w \in W \}, V \rangle$ where
  - $W = 2^{ATM}$ the set of **all** logically possible worlds (= all truth assignments)
  - $\leq_w$ is a 'faithful' partial pre-order:
    - $w \leq_w u$ for all $u$
    - if $u \leq_w w$ then $u = w$

    consequence: $\min_{\leq_w}(W) = \{w\}$
  - $V(w) = w$ (every $w$ is a set of atoms)

# The KM-postulates

(U1) $B{\leftarrow\!\diamond}A \rightarrow A$

(U2) If $B \rightarrow A$ then $B{\leftarrow\!\diamond}A \leftrightarrow B$

(U3) If $B$ and $A$ are consistent, then $B{\leftarrow\!\diamond}A$ is consistent.

(U4.1) If $B_1 \leftrightarrow B_2$ then $B_1{\leftarrow\!\diamond}A \leftrightarrow B_2{\leftarrow\!\diamond}A$

(U4.2) If $A_1 \leftrightarrow A_2$ then $B{\leftarrow\!\diamond}A_1 \leftrightarrow B{\leftarrow\!\diamond}A_2$

(U5) $(B{\leftarrow\!\diamond}A) \wedge C \rightarrow B{\leftarrow\!\diamond}(A \wedge C)$

(U6) If $(B{\leftarrow\!\diamond}A_1) \rightarrow A_2$ and $(B{\leftarrow\!\diamond}A_2) \rightarrow A_1$ then $B{\leftarrow\!\diamond}A_1 \leftrightarrow B{\leftarrow\!\diamond}A_2$

(U7) $(B{\leftarrow\!\diamond}A_1) \wedge (B{\leftarrow\!\diamond}A_2) \rightarrow B{\leftarrow\!\diamond}(A_1 \vee A_2)$
if $B$ is complete (requires finite language!)

(U8) $(B_1 \vee B_2){\leftarrow\!\diamond}A \leftrightarrow (B_1{\leftarrow\!\diamond}A) \vee (B_2{\leftarrow\!\diamond}A)$

**Theorem:** sound and complete for finite languages

©Herzig and Wassermann, 2001 

# Lecture 5

# Computational Models of Update

material from (Herzig & Rifi, AIJ 1999), with **minimal changes** only ...

- concrete update operations
- handling of disjunctive input
- status of the KM-postulates
- handling of integrity constraints

©Herzig and Wassermann, 2001

# KM theory and the desiderata

- success = (U1)
- syntax-independence = (U4.1) + (U4.2),
- consistency ‘as much as possible’ = (U3)
- minimal change

  . . . not always satisfied

©Herzig and Wassermann, 2001 

# KM-theory and minimal change

- faithful partial pre-order for maximal change:

$$\leq_w = \{\langle w, u\rangle | u \in W\}$$

- consequence:

$$\min_{\leq_w}([A]) = \begin{cases} \{w\} & \text{if } w \in [A] \\ [A] & \text{else} \end{cases}$$

- the maximal change operation

$$B \leftarrow\!\!\diamond A \leftrightarrow \begin{cases} B \text{ if } B \vdash A \\ A \text{ if } B \nvdash A \end{cases}$$

is a KM-update operation!

©Herzig and Wassermann, 2001 

# Minimal change: intuitions

- exclude the maximal change pre-order
- focus on orderings such that

$$\emptyset \leq_\emptyset \{p\} \leq_\emptyset \{p,q\}$$

($\{p\}$ closer to $\emptyset$ than $\{p,q\}$)

- guarantees $(\neg p \wedge \neg q) \leftarrow\!\!\diamond p \ \rightarrow \ \neg q$

**unique orderings . . .**

©Herzig and Wassermann, 2001

# Forbus' semantics – 1

(Forbus, IJCAI 1989)

- particular KM closeness relation $\leq_w$
- unique model
- distance-based:

$$dist_F(w,u) = \text{the number of atoms whose truth value differs}$$

- $dist_F(\emptyset,\{p\}) = 1$
  $dist_F(\emptyset,\{p,q\}) = 2$
  $dist_F(\{p\},\{q\}) = 2$
- revision counterpart: (Dalal, AAAI 1988)

©Herzig and Wassermann, 2001 

# Forbus' semantics – 2

- $dist_F$ induces faithful total pre-order:
  $u \leq_w v$ iff $dist_F(w,u) \leq dist_F(w,v)$
- $\emptyset <_\emptyset \{p\} <_\emptyset \{p,q\}$
- $w \cdot [A] = \min_{\leq_w}([A])$
  $= \{u|$ there is no $u'$ such that $dist_F(w,u') < dist_F(w,v)$
- $(\neg p \wedge \neg q) \longleftarrow\!\diamond p \leftrightarrow (p \wedge \neg q)$

- too strong?

$$(\neg p_1 \wedge \neg p_2 \wedge \neg p_3) \longleftarrow\!\diamond (p_1 \vee (p_2 \wedge p_3)) \leftrightarrow (p_1 \wedge \neg p_2 \wedge \neg p_3)$$

©Herzig and Wassermann, 2001 

# The Possible Models Approach (*PMA*)

(Winslett, AAAI 1988)

- $dist(w,u)$ = the set of atoms whose truth value differs

  $dist(\emptyset, \{p_1\}) = \{p_1\}$
  $dist(\emptyset, \{p_2, p_3\}) = \{p_2, p_3\}$
  $dist(\{p_2\}, \{p_3\}) = \{p_2, p_3\}$

- *dist* induces faithful partial pre-order:

  $u \leq_w v$ iff $dist(w,u) \subseteq dist(w,v)$

- $(\neg p_1 \wedge \neg p_2 \wedge \neg p_3) \longleftrightarrow \diamond(p_1 \vee (p_2 \wedge p_3)) \leftrightarrow (p_1 \vee (p_2 \wedge p_3))$

©Herzig and Wassermann, 2001 

# The *PMA*: critiques – 1

- example: throwing a coin on a chessboard [Reiter]




  - $B = \neg Black \wedge \neg White$
  - $A = Black \vee White$
  - $B \leftarrow\!\!\diamond A \;\rightarrow\; \neg(Black \wedge White)$

©Herzig and Wassermann, 2001 

# The *PMA*: critiques – 2

- another example:
  - I believe Kaurismäki lives in SW Finland.
  - I learn that he does not live in SW Finland any longer.
  - Conclusion: he does not live in NE Finland.

  $(South \wedge West) \leftrightarrow\!\!\!\!\!\rightarrow \Diamond(\neg South \vee \neg West) \rightarrow (South \vee West)$
- exclusive interpretation of disjunctive updates:

$$\frac{B \rightarrow \neg(A_1 \vee A_2)}{B \leftrightarrow\!\!\!\!\!\rightarrow \Diamond(A_1 \vee A_2) \rightarrow \neg(A_1 \wedge A_2)}$$

- corrections based on minimal distance:
  *MCD* (Zhang & Foo 1996); *MCD** (Herzig & Rifi 1998)
  . . . but there are counterexamples

**updates cannot be based on minimizing distances**

©Herzig and Wassermann, 2001 

# The *PMA*: generalizing the critiques

**Theorem (Herzig & Rifi 1998):**
Suppose

- $\leftarrow\!\!\diamond$ satisfies the KM postulates (U1) and (U5);
- $A_1$ and $A_2$ are independent: $B \leftarrow\!\!\diamond A_1 \rightarrow \neg A_2$ and $B \leftarrow\!\!\diamond A_2 \rightarrow \neg A_1$.

Then

$$B \leftarrow\!\!\diamond (A_1 \vee A_2) \;\rightarrow\; \neg(A_1 \wedge A_2)$$

– unintuitive property for updates (but rational for revision!)

– KM theory must be abandonned

– updates cannot be based on orderings

©Herzig and Wassermann, 2001 

# Lecture 5, half way

Computational models of update

- KM-semantics, based on a particular ordering
  - *FORBUS*, *PMA*, *MCD*, *MCD**
  - critique: handling of disjunctive input
- back to selection function semantics

©Herzig and Wassermann, 2001

# Winslett's Standard Semantics (*WSS*)

(Winslett 1990)

- $w \cdot A = \{v \in [A] | dist(w,v) \subseteq atm(A)\}$
- $atm(A)$ = set of atoms occurring in $A$
- $atm(A)$ : set of atoms allowed to change
- 'syntax-based' ($w \cdot A$ instead of $w \cdot [A]$)
- $B \leftarrow\!\diamond South \not\leftrightarrow B \leftarrow\!\diamond (South \wedge (West \vee \neg West))$

# $WSS\downarrow$ = *WSS* plus normal forming

(Herzig & Rifi, ECAI 1998)

- eliminate redundant atoms:
  $(p \wedge (q \vee \neg q))\downarrow = p$
- $p$ redundant in $A$ iff $A[p := \top] \leftrightarrow A[p := \bot]$
- $A\downarrow$: no redundant atoms
- $w \cdot A = \{v \in [A] | dist(w,v) \subseteq atm(A\downarrow)\}$
- syntax-independent:
  if $A \leftrightarrow A'$ then $w \cdot A = w \cdot A'$
- equivalent proposal: *MPMA* (Doherty et al., KR 1998)
- similar but more conservative: *MCE* (Zhang & Foo 1996)

©Herzig and Wassermann, 2001 

# $WSS\downarrow$ and the KM-theory

(U1) $B \leftarrow\!\diamond A \rightarrow A$

(U2.1) If $B \rightarrow A$ then $B \rightarrow B \leftarrow\!\diamond A$

(U2.2) If $B \rightarrow A$ then $B \leftarrow\!\diamond A \rightarrow B$

(U3) If $B$ and $A$ are consistent, then $B \leftarrow\!\diamond A$ is consistent.

(U4.1) If $B_1 \leftrightarrow B_2$ then $B_1 \leftarrow\!\diamond A \leftrightarrow B_2 \leftarrow\!\diamond A$

(U4.2) If $A_1 \leftrightarrow A_2$ then $B \leftarrow\!\diamond A_1 \leftrightarrow B \leftarrow\!\diamond A_2$

(U5) $(B \leftarrow\!\diamond A) \wedge C \rightarrow B \leftarrow\!\diamond (A \wedge C)$

(U6) If $(B \leftarrow\!\diamond A_1) \rightarrow A_2$ and $(B \leftarrow\!\diamond A_2) \rightarrow A_1$ then $B \leftarrow\!\diamond A_1 \leftrightarrow B \leftarrow\!\diamond A_2$

(U7) $(B \leftarrow\!\diamond A_1) \wedge (B \leftarrow\!\diamond A_2) \rightarrow B \leftarrow\!\diamond (A_1 \vee A_2)$ if $B$ is complete

(U8) $(B_1 \vee B_2) \leftarrow\!\diamond A \leftrightarrow (B_1 \leftarrow\!\diamond A) \vee (B_2 \leftarrow\!\diamond A)$

**(U2.2), (U5), (U6), (U7) violated**

©Herzig and Wassermann, 2001 

# $WSS\downarrow$: a critique of the violated postulates

(U7) $(B \leftarrow\!\diamond A_1) \wedge (B \leftarrow\!\diamond A_2) \rightarrow B \leftarrow\!\diamond (A_1 \vee A_2)$ if $B$ is complete

'technical' postulate to ensure completenes of KM theory
(makes no sense if language is infinite)

(U6) If $(B \leftarrow\!\diamond A_1) \rightarrow A_2$ and $(B \leftarrow\!\diamond A_2) \rightarrow A_1$ then $B \leftarrow\!\diamond A_1 \leftrightarrow B \leftarrow\!\diamond A_2$

entails (U2.2) under $B \leftarrow\!\diamond \top \rightarrow B$: hence v. (U2.2)

(U5) $(B \leftarrow\!\diamond A) \wedge C \rightarrow B \leftarrow\!\diamond (A \wedge C)$

v. handling of disjunctive input

(U2.2) If $B \rightarrow A$ then $B \leftarrow\!\diamond A \rightarrow B$

...

©Herzig and Wassermann, 2001 

# Reexamining the explanation of updates

1. belief base $B$ = what is believed by an agent about the 'the actual world'
2. sensors information $A$ about facts of the actual world
3. $A$ describes an event in the actual world
4. agent changes $B$ such that $B \leftarrow\!\!\diamond A$ as close as possible to what agent believes to know about the actual world
5. sensing can be noisy
6. agent ignores whether there is misperception or not

©Herzig and Wassermann, 2001 

# $WSS\downarrow$: a critique of conservativity (U2.2)

(U2.2) If $B \rightarrow A$ then $B \leftarrow\!\diamond A \rightarrow B$

- in $WSS\downarrow$
  $p \leftarrow\!\diamond (p \vee q) \leftrightarrow (p \vee q)$
- example:
  - A coin shows heads (*Heads*).
  - Somebody tosses the coin, but I can't see the outcome (*Heads* $\vee$ *Tails*).
  - $Heads \leftarrow\!\diamond (Heads \vee Tails) \leftrightarrow (Heads \vee Tails)$

©Herzig and Wassermann, 2001 

# Integrity constraints – 1

alias domain constraints, domain laws, ...

$$IC = \neg(Heads \wedge Tails)$$

- wanted:
  $Heads \leftarrow\!\diamond_{IC} Tails \;\rightarrow\; \neg Heads$
- standard proposal:

$$B \leftarrow\!\diamond_{IC} A \;=\; B \leftarrow\!\diamond (A \wedge IC)$$

- $Heads \leftarrow\!\diamond (Tails \wedge \neg(Heads \wedge Tails)) \;\leftrightarrow Heads \wedge \neg Tails$

©Herzig and Wassermann, 2001 

# Integrity constraints – 2

- counterexample (Ginsberg):




  - $IC = (Up_1 \leftrightarrow Up_2) \leftrightarrow Light$
    $B = Up_1 \wedge Up_2 \wedge Light$
    $A = \neg Up_1$
  - intuitively: $B \leftarrow\!\!\diamond A \ \rightarrow \ Up_2$
  - . . . but not the case in $PMA$, $MCD$, $MCD^*$, $WSS$, $WSS\downarrow$

**alternative definitions of $B \leftarrow\!\!\diamond_{IC} A$?**

©Herzig and Wassermann, 2001 

# $WSS^{dep}$ = *WSS* plus dependence

(Herzig 1996)

- hypothesis: dependence function *dep*

$$dep(Up_1) = \{Up_1, Light\}$$

(given)

- $w \cdot A = \{v \in [A] | dist(w,v) \subseteq depA\}$
- $Up_2 \notin dep(Up_1)$:

$$\{Up_1, Up_2, Light\} \cdot Up_1 \subseteq [Up_2]$$

can be made syntax-independent by normal forming: $WSS\downarrow^{dep}$

similar proposal, but based on relation of causality:
$MPMA^{\gg}$(Doherty et al., KR 1998)

©Herzig and Wassermann, 2001 

# Overview: the desirable KM postulates

| | (U1) | (U2.1) | (U3) | (U4) | (U8) |
|---|---|---|---|---|---|
| ***FORBUS*** | y | y | y | y | y |
| ***PMA*** | y | y | y | y | y |
| ***MCD*** | y | y | y | y | y |
| ***MCD**** | y | y | y | y | y |
| ***WSS*** | y | y | y | n | y |
| $WSS\downarrow$ | y | y | y | y | y |
| ***MCE*** | y | y | y | y | y |
| $WSS^{dep}$ | y | y | y | n | y |
| $WSS\downarrow^{dep}$ | y | y | y | y | y |
| $MPMA^{\gg}$ | y | y | y | y | y |

©Herzig and Wassermann, 2001 

# Overview: the undesirable KM postulates

| | (U2.2) | (U5) | (U6) | (U7) |
|---|---|---|---|---|
| ***FORBUS*** | y | y | y | y |
| ***PMA*** | y | y | y | y |
| ***MCD*** | y | n | y | n |
| ***MCD**** | y | n | y | n |
| ***WSS*** | n | n | n | y |
| $WSS\downarrow$ | n | n | n | n |
| ***MCE*** | y | n | y | n |
| $WSS^{dep}$ | n | n | n | y |
| $WSS\downarrow^{dep}$ | n | n | n | n |
| $MPMA^{\gg}$ | n | n | n | n |

©Herzig and Wassermann, 2001 

# Overview: comparative strength



# Overview: complexity

- PSPACE-complete:
  $MCD*$
- $\Pi_2^p$-complete:
  $PMA$, $FORBUS$, $MCD$, $MCE$
- coNP-complete:
  $WSS$, $WSS{\downarrow}$, $WSS^{dep}$, $WSS{\downarrow}^{dep}$, $MPMA^{\gg}$

©Herzig and Wassermann, 2001 

# To conclude

- We started from selection function semantics . . .
- . . . refined minimal change:
  - closeness orderings
  - KM theory: faithful partial pre-orders of closeness
  - *FORBUS*, *PMA*: unique pre-order
- . . . criticized KM theory:
  - handling of disjunctions
  - conservativity
  - handling of integrity constraints
- . . . to finally get back to selection functions!
  - based on dependence

©Herzig and Wassermann, 2001 

# Bibliography


- Standard AGM:
  - Carlos Alchourrón, Peter Gärdenfors, and David Makinson, On the logic of theory change. Journal of Symbolic Logic, 1985.
  - Carlos Alchourrón and David Makinson, On the logic of theory change: safe contraction. Studia Logica, 1985.
  - Adam Grove, Two modellings for theory change. Journal of Philosophical Logic, 1988.
  - Peter Gärdenfors, Knowledge in Flux, MIT Press, 1988.
  - Peter Gärdenfors and David Makinson, Revision of Knowledge Systems using Epistemic Entrenchment. Proceedings of TARK, 1988.
  - Peter Gärdenfors and Hans Rott, Belief Revision. Handbook of Logic in Artificial Intelligence and Logic Programming, vol. 4, 1995.

- Base Dynamics:
  - Sven Ove Hansson, A Textbook of Belief Dynamics, Kluwer, 1999.
  - Bernhard Nebel, Reasoning and Revision in Hybrid Representation Systems. Volume 422 of Lecture Notes in AI, Springer-Verlag, 1990.
- New Trends in Revision:
  - Sven Ove Hansson, A Survey of Non-prioritized Belief Revision. Erkenntnis, 1999.
  - David Makinson, Screened Revision. Theoria, 1997.
  - Eduardo Fermé and Sven Ove Hansson, Selective Revision. Studia Logica, 1999.
  - Sven Ove Hansson and Renata Wassermann, Local Change. To appear in Studia Logica.
  - Renata Wassermann, On Structured Belief Bases. Frontiers in Belief Revision, Kluwer, 2001.
  - Marco Schaerf and Marco Cadoli, Tractable Reasoning via

Approximation. Artificial Intelligence, 1995.

- Samir Chopra, Rohit Parikh and Renata Wassermann, Approximate Belief Change. To appear in the Journal of the IGPL.

- Theory of update, update vs. revision
  - A.M. Keller and M. Winslett, On the use of an extended relational model to handle changing incomplete information. In IEEE Transactions on Software Engineering, 1985.
  - Hirofumi Katsuno and Alberto O. Mendelzon, On the difference between updating a knowledge base and revising it. In Belief revision. Cambridge University Press, 1992. (preliminary version in Proc. KR'91)

- The Ramsey test
  - Peter Gärdenfors, Conditionals and changes of belief. In I. Niiniluoto and R. Tuomela, editors, The Logic and Epistemology of Scientific Change, volume 30, Acta Philosophica Fennica, 1978.
  - Gösta Grahne, Updates and counterfactuals. Proc. KR'91, 1991.

- Mark Ryan and Pierre-Yves Schobbens, Intertranslating counterfactuals and updates. In J. of Logic, Language and Information, 6(2):123–146, 1997.
- Andreas Herzig, Logics for belief base updating. In Handbook of defeasible reasoning and uncertainty management, vol. 3. Kluwer Academic Publishers, 1998.
- David Makinson, The Gärdenfors impossibility theorem in non-monotonic contexts. Studia Logica, 49:1–6, 1992.
- Frank Wolter, A counterexample in tense logic. Notre Dame J. of Formal Logic, 37(2), 1997. (special issue on combining logics).
- Heinrich Wansing, Sequent Calculi for Normal Modal Propositional Logics. In Journal of Logic and Computation, 4:125–42, 1994.


- conditional logic
  
  - Robert Stalnaker, A theory of conditionals. Studies in Logical Theory, American Philosphical Quarterly. Blackwell, Oxford, 1968.
  

- Brian Chellas, Basic conditional logics. In J. of Philosophical Logic, 4:133–153, 1975.
- John Burgess, Quick completeness proofs for some logics of conditionals. Notre Dame J. of Formal Logic, 22:76–84, 1981.
- David Lewis, Counterfactuals. Basil Blackwell, Oxford, 1973.

- Computational models of update
  - Mary-Anne Winslett, Reasoning about action using a possible models approach. In Proc. AAAI'88, 1988.
  - Mary-Anne Winslett, Updating Logical Databases. Cambridge Tracts in Theoretical Computer Science. Cambridge University Press, 1990.
  - Kenneth D. Forbus, Introducing actions into qualitative simulation. In Proc. IJCAI'89, 1989.
  - Mukesh Dalal, Investigations into a theory of knowledge base revision: preliminary report. In Proc. AAAI'88, 1988.
  - Andreas Herzig, The PMA revisited. In Proc. KR'96, 1996.
  - Yan Zhang and Norman Y. Foo, Updating knowledge bases with

disjunctive information. In Proc. AAAI'96, 1996.

- Andreas Herzig and Omar Rifi, Update operations: a review. In Proc. ECAI'98, 1998.
- P. Doherty, W. Łukaszewicz, and E. Madalinska-Bugaj, The PMA and relativizing change for action update. In Proc. KR'98, 1998.
- Andreas Herzig and Omar Rifi, Propositional belief base update and minimal change. In Artificial Intelligence Journal, 115(1):107-138, 1999.

# For More Information

**Andreas Herzig:** `www.irit.fr/~Andreas.Herzig`

**Renata Wassermann:** `www.ime.usp.br/~renata`

©Herzig and Wassermann, 2001 